

- PUSH BUTTON & REMOTE START
 Pull cord backup
- QUIET & DURABLE Double-insulated
- PARALLEL CAPABLE
 Capable of paralleling with another P4500 inverter generator.

FUEL EFFICIENT

3.4 gallon fuel tank that runs 18 hrs at 25% load

LIGHTWEIGHT

At 98 lbs, and with a telescopic handle and wheels it's lighter and easier to manage.



Onan P4500i

Inverter Generator Features and Specifications

- RV and camper ready with 30A TT-30R outlet
- Two 5V USB ports for charging sensitive electronics such as phones or tablets
- Telescoping handle and wheels for easy transportation

- Dependable 7.3 HP 224cc OHV 4-Stroke engine
- Parallel capable with another P4500 inverter generator to reach 50A of power
- 3-Year Warranty

| De d.M. subset | A05011055 |
|--|---|
| Part Number | A058U955 |
| Gasoline Peak Watts | 4500 |
| Gasoline Running Watts | 3700 |
| Peak Amps at 120V | 37.5 amps |
| Running Amps at 120V | 30.8 amps |
| AC Voltage | 120 Volts |
| DC Voltage | 5 Volts |
| AC Frequency | 60 Hz |
| Parallel Capable | Yes |
| Engine Horse Power (HP) | 7.3 HP |
| Total Harmonic Distortion (THD) | <3% |
| Automatic Voltage Regulator (AVR) | Yes |
| Starting System | Electric, Remote, Recoil |
| Battery Included | Yes |
| Battery Charger Included | Yes |
| Remote Start Fob Included | Yes |
| Themote Start Fob included | (paired at factory) |
| Remote Start Distance (yards/meters) | 109 yd. (100 m.) |
| Engine Displacement | 224cc |
| Engine Brand | Ducar |
| Engine Type | OHV 4 Stroke |
| Engine Speed | Variable |
| Engine RPM | Max 3600 |
| Operational Volume | As low as 52 dBA |
| Spark Plug (included) | Torch E6RTC |
| Carburetor Kit Required to Operate at Altitude | Yes, above 2000ft |
| Economy Mode Switch | Yes |
| Built-in Inverter | Yes |
| Engine Lubrication | Splash |
| Recommended Oil | SAE 10W30 |
| Oil Bottle Size (included) | .6 qt. (20.3 oz.) |
| Oil Capacity (Quarts/Ounces) | .6 qt. (20.3 oz.) |
| Low Oil Shutdown | Automatic |
| Fuel Type | Unleaded Gasoline, 10% Ethanol or less |
| Fuel Shut Off | Manual |
| Fuel Tank Material | Steel |
| Fuel Tank Capacity (Gallons/Liters) | 3.4 gal. (12.8 L) |
| Run Time at %25 Load (hrs.) | 18 hrs. |
| , , | |

| Run Time at %50 Load (hrs.) | 15 hrs. |
|---------------------------------------|---|
| Gasoline Fuel Gauge | Yes |
| Choke type | Automatic |
| AC Outlets | (1) 120V 30A (TT-30R) (1) Duplex 120V 20A (5-20R) |
| DC Outlets | (2) 5V USB ports |
| Ground | Floating Neutral |
| Covered Outlets | Yes |
| Transfer Switch Ready | No |
| GFCI Outlets | No |
| LED Data Center | Yes |
| RV Ready Outlet | Yes |
| Overload Protection (circuit breaker) | Yes |
| Handle Style | Telescoping Handle |
| Emissions | EPA, CARB |
| Canada CSA Compliant | Yes |
| Wheel Kit Included | Yes (assembled) |
| Wheel Size | 5.5 in. Diameter, 1.5 in. Thick |
| Spark Arrestor | Yes |
| Residential Warranty | 3 Years |
| Commercial Warranty | 1 Year |
| Assembled Length in. (mm) | 24.5 in. (622 mm) |
| Assembled Width in. (mm) | 18.25 in. (463 mm) |
| Assembled Height in. (mm) | 20.5 in. (520 mm) |
| Carton Length in. (mm) | 30.3 in. (768 mm) |
| Carton Width in. (mm) | 19.5 in. (495 mm) |
| Carton Height in. (mm) | 21 in. (533 mm) |
| Dry Unit Weight lb. (kg) | 98 lb. (44 kg) |
| Shipping Weight lb. (kg) | 104 lb. (47 kg) |





cummins.com



Twitter.com/CumminsFacebook.com/Cummins

YouTube.com/Cummins

