

TRAK™

The Trak modern commercial ceiling fan collection will update your indoor and outdoor spaces including restaurants, hotels, and sport facilities. The Trak ceiling fan is designed and engineered with a commercial grade motor and extracted aluminum blades for a long lifespan and optimal airflow in large, open spaces.







MOTOR	Reversible, 8-speed DC Motor			
SIZES AVAILABLE	60", 72", 84", 96"			
LIGHT VERSION	30W LED, 900 Lumens, LM/W 30			
MOTOR CONTROL	120v Single Phase 50/60hz 240v Single Phase 50/60hz			
LOCATION	Indoor & Outdoor. IP 45			
BLADES MATERIAL	6061-T6 Aircraft Grade aluminum			
HOUSING MATERIAL	Plastic			
SAFETY CABLE	1/4" 7x19 Safety Cable			
INSTALLATION	Easy Installation			
CONTROL OPTIONS	Remote Control included. BMS integration.			
DOWNROD SIZES	24", 36", 48", 60", not available 72"			
WARRANTY	3 years			

Technical Specifications											
Diameter	Location	Input Power	Power	Max Amps	Max. Affected Area	Max Velocity	CFM*	Watts at Max*	Weight		
60"/(1.52 m)	Indoor Outdoor	120V/ 50-60HZ	0.13 HP	1.16 A	20ft diameter / 400 sq. ft 6m diameter / 37.16 m ²	9.82 MPH 4.39 M/S	13,032.00	91.2	48 Lbs 21.77 Kgs		
72"/(1.82 m)	Indoor Outdoor	120V/ 50-60HZ	0.13 HP	1.16 A	24ft diameter / 576 sq. ft 7.31m diameter / 53.51 m ²	9.31 MPH 4.16 M/S	17,895.00	103	45.8 Lbs 22 Kgs		
84"/(2.13 m)	Indoor Outdoor	120V/ 50-60HZ	0.13 HP	1.16 A	28ft diameter / 784 sq. ft 8.53m diameter / 72.83 m²	8.51 MPH 3.80 M/S	22,110.00	90.7	49 Lbs 22.22 Kgs		
96"/(2.43 m)	Indoor Outdoor	120V/ 50-60HZ	0.13 HP	1.16 A	32ft diameter / 1,024 sq. ft 9.75m diameter / 95.13 m ²	8 MPH 3.57 M/S	24,758.00	118.70	49.5 Lbs 22.45 Kgs		